







CCEA Chicago Plenum rated & Airtight(1)

## **SMART BOX**

Designers can stay up all night trying all sorts of things with Smart, Modular L.I.'s most versatile range of architectural lighting. Mix and match, from a mosaic of shapes, sizes, colors and mounting options, and create a playful installation while maintaining a consistent look and feel. The Smart choice for any application.

## 3 designs that multiply

Smart's 3 designs are already a party for designers. Fun, curvy shapes, small and charming. Double the fun, Lotis, Cake and Kup come in fixed and adjustable versions. Adding color to double fun, all variations are available in black structure, white structure and a warm, golden finish, and can further be combined with all Smart accessories. How's that for a party?

## Limitless combinations

A list of accessories lets you play with shapes and depth. Smart box adds dimension by protruding from the ceiling, hugging any of the 3 designs in any of 3 the colors.

## Smart things in little packages

Smart is welcoming a new cylinder accessory that also acts as a low voltage electrical connection box. Together with a remote driver this allows mounting without a typical junction box (although a junction box can still be used if already in place). Yep, this means easier installation and the ability to connect multiple fixtures back to one remote driver. Try it mounted on the ceiling, in its suspended version or surface-mounted on a wall with up and down light.

versions 3 spotlight options:

Cake, Kup, Lotis - fixed & adjustable

lamp units 3.2" adjustable - Cake, Lotis, Kup

3.2" adjustable - Cake, Lotis, Kup 3.2" fix - Cake, Lotis, Kup 4.5" adjustable - Cake, Lotis, Kup 4.5" fix - Cake, Lotis, Kup

colors black structure, gold, white structure

mounting plaster plate for 4"x4" jbox

(surface/suspended/wall)

accessories cover plates

output\* 3.2" adjustable - up to 717lm

3.2" fix - up to 840lm 4.5" adjustable - up to 773lm 4.5" fix - up to 1630lm

oower 3.2", 4.5" adjustable - 9.2W

4.5" fix - 16.2W

cct 2700K, 3000K, 3500K

cri >90, R9>50

optics 3.2" adjustable - 25°, 40°, clear

3.2" fix - 15°, 25°, 40°, clear, frosted, micro

prismatic

4.5" adjustable - 15°, 25°, 40°, clear 4.5" fix - 15°, 25°, 40°, clear, frosted, micro

prismatic

voltage 120-277V

dimming *EldoLED 0-10V, ELV/Triac/0-10V* adjustability *3.2" adjustable - h 355° v 25° 4.5" adjustable - h 355° v 30°* 

location damp rated

-

more info? supermodular.com/en-us/smart-box/



















